

HKV 914-SS SERIES HYDRAULIC 3-WAY AISI 316-L STAINLESS STEEL BALL VALVES

Body Material	: AISI 316 stainless steel
Ball Material	: AISI 316 stainless steel
Thread Size	: BSP (Upon Request: NPT, Metric)
Ball Seats	: Delrin (POM)
Sealing	: Nitrile O-ring (NBR)
Working Temperature:	-30 °C and +110 °C
Upon Request	: VITON, EPDM (For steam application) (-30°C -+ 225°C)
Applications	: Marine, food, pharmacy, medical, chemical, irrigation, paper, paint, textile, gas and aviation



Product Description

HKV914SS Series 2-Way AISI 316-L Stainless Steel Ball Valves are completely made of AISI 316-L stainless steel row material have an excellent resistance to all kind of chemical and corrosion.

HKV914SS Series Ball Valves can be locked in the open or closed position through locking washer on the circle pin.

Technical Features

CODE	THREAD SIZE/K	WORKING PRESSURE - bar	DIMENSIONS - mm									
			A	B	C	D	E	F	G	L	M	
HKV 914-SS.01	1/4" BSP	500	45	35	30	77	142	24	48	75	DN 10	
HKV 914-SS.02	3/8" BSP	500	45	35	30	77	142	24	48	75	DN 10	
HKV 914-SS.03	1/2" BSP	500	50	40	35	82	147	30	53,50	84	DN 13	
HKV 914-SS.04	3/4" BSP	400	60	55	45	111	221	38	73	96	DN 20	
HKV 914-SS.05	1" BSP	400	70	60	55	116	235	46	78	118	DN 25	
HKV 914-SS.06	1 1/4" BSP	400	70	60	55	116	235	50	78	134	DN 25	
HKV 914-SS.07	1 1/2" BSP	380	70	60	5	116	235	55	78	140	DN 25	

Technical Features

HKV 914-SS Series Hydraulic 2-Way AISI 316-L Stainless Steel Ball Valves- Welded Sheet Connection

CODE	SIZE/K	DIMENSIONS - mm							
		N	O	P	R	S	T	U	V
HKV 914-SS.01	1/4" BSP	27.50	47.50	40	60	6.25	6.25	6.50	4
HKV 914-SS.02	3/8" BSP	27.50	47.50	40	60	6.25	6.25	6.50	4
HKV 914-SS.03	1/2" BSP	30.50	54.50	45	67	6.25	7.25	6.50	4
HKV 914-SS.04	3/4" BSP	40.50	64.50	55	79	7.25	7.25	9	4
HKV 914-SS.05	1" BSP	50.50	74.50	65	89	7.25	7.25	9	4
HKV 914-SS.06	1 1/4" BSP	50.50	74.50	65	89	7.25	7.25	9	4
HKV 914-SS.07	1 1/2" BSP	50.50	74.50	65	89	7.25	7.25	9	4

