

Steam Solenoid Valves S2073 Series (G1/8", G1/4", G3/8", G1/2")

GENERAL FEATURES

- Wide pressure range, flow rate and orifis options.
- Solenoid valves are used with filters.
- Solenoid valves can be mounted in any position without affecting its operation.
- Coil to be used in a vertical position.

ELECTRICAL CHARACTERISTICS

Continuous Duty	: ED %100
Coil Insulation Class	: H (180°C)(IEC 85)
Coil Impregnation	: Polyester Fiber Glass
Ambient Temperature	: -10°C, +60°C
Protection Degree	: IP65 (ISO 60529) On request; IP68
Electric Plug Connection	: DIN 46340 3-Poles Connector (DIN 43650)
Connector Specification	: ISO 4400 / EN 175301-803 Form A, Spade Plug (Cable Ø6-8 mm)
Electrical Safety	: IEC 335
Standard Voltages	: AC 12V 15VA, 24V 15VA, 48V 15VA, 230V 15VA, 230V 24VA DC 12V 18W, 24V 18W, 48V 18W, 110V 18W

On request other voltages

Voltages Tolerance : AC -15%, +10% DC -5%, +10%

Frequency : 50 Hz (60 Hz...)

On request; Connector with LED, PWM Socket Specify coil voltage with order

MATERIALS IN CONTACT WITH FLUID

Body	: Brass
Internal Parts	: Stainless Steel
Sealing	: EPDM,
Shading Ring	: Copper (EN 12735-1)
Seats, Core Tube, Springs	: Stainless Steel

OPTIONS

Female connection: BSP; (On request NPT)

- On request CR-Ni plated,
- On request Atex (exproof) coil.

TECHNICAL FEATURES

Max. Viscosity : 5°E (-37cST veya mm²/s)

Response Time : Opening time : 30 ms
Closing Time : 30 ms



NORMALLY CLOSED

2/2 WAY


DIRECT ACTING



STEAM

Dimensions (mm)

G	A	B	C	D	E	F	H
1/8"	35,5	67	32	39	74,5	24,5	18
1/4"	35,5	67	32	39	74,5	24,5	18
3/8"	50	73	32	39	82,5	26,5	-
1/2"	50	73	32	39	82,5	26,5	-



Coils	Nominal Values	Cold/ Hot	Inrush	Holding	Current (A)	Surface Temperature (°C)
C40012VDC18W	12VDC 18W	COLD HOT	19,56 14,52	19,56 14,52	1,63 1,21	20 106
C40024VDC18W	24VDC 18W	COLD HOT	20,88 14,64	20,88 14,64	0,87 0,61	25 116
C40110VDC18W	110VDC 18W	COLD HOT	19,96 13,56	19,96 13,56	0,18 0,123	23 115
C40012VAC15VA	12VAC 15VA	COLD HOT	23,81 -	16,43 15,86	1,3 1,262	25 79
C40024VAC15VA	24VAC 15VA	COLD HOT	25,82 -	15,02 13,91	0,62 0,57	22 81
C40110VAC15VA	110VAC 15VA	COLD HOT	30,65 -	15,17 13,96	0,137 0,126	24 80
C40230VAC15VA	230VAC 15VA	COLD HOT	31,4 -	15,64 14,41	0,068 0,063	25 80
C40230VAC24VA	230VAC 24VA	COLD HOT	45,1 -	23,92 21,62	0,0154 0,0154	23 100

Solenoid Valve Symbol	Valve Type/ Order No	Connection Size	Orifice Size	Pressure min/max	Kv	Seal	Weight	Temperature
	S2073	G	mm	Bar Bar	l/min	EPDM	kg	°C
	S2073.00.018	1/8"	1.8	0 5	1.6	✓	0,31	160
	S2073.00.025	1/8"	2.5	0 5	3.2	✓	0,31	160
	S2073.00.030	1/8"	3	0 5	4.6	✓	0,31	160
	S2073.00.040	1/8"	4	0 5	6.4	✓	0,31	160
	S2073.00.045	1/8"	4.5	0 5	7.5	✓	0,31	160
	S2073.01.018	1/4"	1.8	0 5	1.6	✓	0,30	160
	S2073.01.025	1/4"	2.5	0 5	3.2	✓	0,30	160
	S2073.01.030	1/4"	3	0 5	4.6	✓	0,30	160
	S2073.01.040	1/4"	4	0 5	6.4	✓	0,30	160
	S2073.01.045	1/4"	4.5	0 5	7.5	✓	0,30	160
	S2073.02.030	3/8"	3	0 5	4.6	✓	0,4	160
	S2073.02.040	3/8"	4	0 5	6.4	✓	0,4	160
	S2073.02.050	3/8"	5	0 5	9.2	✓	0,4	160
	S2073.03.030	1/2"	3	0 5	4.6	✓	0,38	160
	S2073.03.040	1/2"	4	0 5	6.4	✓	0,38	160
	S2073.03.050	1/2"	5	0 5	9.2	✓	0,38	160

STANDARDS

• Standard tube connection G (BSP) (ISO 228-1) and other tube connections (NPT (ANSI 1.20.3)) are available on request.

• TORK solenoid valves 97/23/EC, are available for pressure equipment directive (PED) and 2006/95/ECC low voltage directive (LVD)..

Not: Please look catalogues for more details