

Compressor Solenoid Valve S5078 Series (G1/8", G1/4")

GENEL ÖZELLİKLER

- Wide pressure range, flow rate and orifices options.
 - Solenoid valves are used with filters.
 - Solenoid valves can be mounted in any position without affecting its operation.
 - Coil to be used in a vertical position.
 - TORK series S5073 direct acting plate mounting compressor solenoid valves are 2/2 way, normally closed and have small body size.
 - Manual override or without manual override, for small body (1/8" and 1/4"), square type body and easy installation
 - On request; manual override
- Working temperature:** -10°C / +160°C
- Don't require any differential pressure.

ELECTRICAL CHARACTERISTICS

Continuous Duty	: ED %100
Coil Insulation Class	: H (180°C)(IEC 85)
Coil Impregnation	: Polyester Fiber Glass
Ambient Temperature	: -20°C, +60°C
Protection Degree	: IP65 (ISO 60529) On request; IP68
Electric Plug Connection	: DIN 46340 3-Poles Connector (DIN 43650)
Connector Specification	: ISO 4400 / EN 175301-803 Form A, Spade Plug (Cable Ø6-8 mm)
Electrical Safety	: IEC 335
Standard Voltages	: AC 12V 15VA, 24V 15VA, 48V 15VA, 230V 15VA, 230V 24VA DC 12V 18W, 24V 18W, 48V 18W, 110V 18W

On request other voltages
Voltages Tolerance : AC -15%, +10% DC -5%, +10%
Frequency : 50 Hz (60 Hz...)
 On request; Connector with LED, PWM Socket Specify coil voltage with order

MATERIALS IN CONTACT WITH FLUID

Body	: Brass
Internal Parts	: Stainless Steel
Sealing	: VITON
Shading Ring	: Copper (EN 12735-1)
Seats, Core Tube, Springs	: Stainless Steel

OPTIONS

- Female connection: BSP; (On request NPT)
- On request CR-Ni plated, PTFE coated done
- On request Atex (exproof) coil.

TECHNICAL FEATURES

Max. Viscosity : 5°E (-37cST veya mm²/s)
Response Time : Opening time : 400 - 1600 ms
 Closing Time : 1000 - 2000 ms


SEALS FEATURES

NBR : -20°C...+80°C
EPDM : -30°C...+130°C
VITON : -20°C...+160°C
PTFE : -10°C...+160°C
RUBY : -10°C...+160°C

STANDARDS

- Standard tube connection G (BSP) (ISO 228-1) and other tube connections (NPT (ANSI 1.20.3)) are available on request.
- TORK solenoid valves 97/23/EC, are available for pressure equipment directive (PED) and 2006/95/ECC low voltage directive (LVD).

Not: Please look catalogues for more details



NORMALLY CLOSED


2/2 WAY

DIRECT ACTING

ΔP=0



COMPRESSOR



On request; solenoid valve can have 4 mounting holes at the bottom of the body.

Dimensions (mm)

	G	A	B	C	D	E	F	I
1/8"	35	78.5	32	39	68	26.5	68	
1/4"	35	78.5	32	39	68	26.5	68	

Coils	Nominal Values	Cold/Hot	Inrush	Holding	Current (A)	Surface Temperature (°C)
C40012VDC18W	12VDC 18W	COLD	19,56	19,56	1,63	20
		HOT	14,52	14,52	1,21	106
C40024VDC18W	24VDC 18W	COLD	20,88	20,88	0,87	25
		HOT	14,64	14,64	0,61	116
C40110VDC18W	110VDC 18W	COLD	19,96	19,96	0,18	23
		HOT	13,56	13,56	0,123	115
C40012VAC15VA	12VAC 15VA	COLD	23,81	16,43	1,3	25
		HOT	-	15,86	1,262	79
C40024VAC15VA	24VAC 15VA	COLD	25,82	15,02	0,62	22
		HOT	-	13,91	0,57	81
C40110VAC15VA	110VAC 15VA	COLD	30,65	15,17	0,137	24
		HOT	-	13,96	0,126	80
C40230VAC15VA	230VAC 15VA	COLD	31,4	15,64	0,068	25
		HOT	-	14,41	0,063	80
C40230VAC24VA	230VAC 24VA	COLD	45,1	23,92	0,0154	23
		HOT	-	21,62	0,0154	100

Solenoid Valve Symbol	Valve Type/Order No	Connection Size	Orifice Size	Pressure min/max		Kv	Seal	Weight
	S5078	G	mm	Bar	Bar	l/min	VITON	kg
	S5078.00.010	1/8"	1	0	100	0.6	✓	0,5
	S5078.00.018	1/8"	1.8	0	16	1.6	✓	0,5
	S5078.00.025	1/8"	2.5	0	12	3.2	✓	0,5
	S5078.00.030	1/8"	3	0	10	4.6	✓	0,5
	S5078.00.040	1/8"	4	0	9	6.4	✓	0,5
	S5078.01.010	1/4"	1	0	100	0.6	✓	0,49
	S5078.01.018	1/4"	1.8	0	16	1.6	✓	0,49
	S5078.01.025	1/4"	2.5	0	12	3.2	✓	0,49
	S5078.01.030	1/4"	3	0	10	4.6	✓	0,49
	S5078.01.040	1/4"	4	0	9	6.4	✓	0,49
	S5078.01.050	1/4"	5	0	7	9.2	✓	0,49

Compressor Solenoid Valve S5078P Series

GENERAL FEATURES

- Wide pressure range, flow rate and orific options.
- Solenoid valves are used with filters.
- Solenoid valves can be mounted in any position without affecting its operation.
- Coil to be used in a vertical position.

ELECTRICAL CHARACTERISTICS

Continuous Duty	: ED %100
Coil Insulation Class	: H (180°C)(IEC 85)
Coil Impregnation	: Polyester Fiber Glass
Ambient Temperature	: -20°C, +60°C
Protection Degree	: IP65 (ISO 60529) On request; IP68
Electric Plug Connection	: DIN 46340 3-Poles Connector (DIN 43650)
Connector Specification	: ISO 4400 / EN 175301-803 Form A, Spade Plug (Cable Ø6-8 mm)
Electrical Safety	: IEC 335
Standard Voltages	: For 3/8"...1" AC 12V 15VA, 24V 15VA, 48V 15VA, 110V 15VA, 230V 15VA DC 12V 18W, 24V 18W, 48V 18W, 110V 18W For 1 1/4"...2" AC 12V 42VA, 24V 42VA, 48V 42VA, 110V 42VA, 230V 42VA DC 12V 35W, 24V 35W, 48V 35W, 110V 35W

On request other voltages

Voltages Tolerance : AC -15%, +10% DC -5%, +10%

Frequency : 50 Hz (60 Hz...)

On request; Connector with LED, PWM Socket Specify coil voltage with order

On request; 3/8"...1" valves can be ATEX

MATERIALS IN CONTACT WITH FLUID

Body	: Brass
Internal Parts	: Stainless Steel
Sealing	: NBR
Shading Ring	: Copper (EN 12735-1)
Seats, Core Tube, Springs	: Stainless Steel

OPTIONS

Female connection: BSP; (On request NPT)

- On request CR-Ni plated, PTFE coated done

TECHNICAL FEATURES

Max. Viscosity	: 5°E (-37cST veya mm²/s)
Response Time	: Opening time : 400 - 1600 ms Closing Time : 1000 - 2000 ms

SEALS FEATURES


NBR	: -20°C...+80°C
EPDM	: -30°C...+130°C
VITON	: -20°C...+160°C
PTFE	: -10°C...+160°C
RUBY	: -10°C...+160°C

STANDARDS

• Standard tube connection G (BSP) (ISO 228-1) and other tube connections (NPT (ANSI 120.3)) are available on request.

• TORK solenoid valves 97/23/EC, are available for pressure equipment directive (PED) and 2006/95/ECC low voltage directive (LVD).

Not: Please look catalogues for more details.



NORMALLY CLOSED



2/2 WAY

PILOT OPERATED

$\Delta P=0,35$



COMPRESSOR



Dimensions (mm)

	G	A	B	C	D	E	F	J	H	I
3/8"	75	97	32	45	91.3	37.5	52	76	108	
1/2"	79	100	32	45	92	39.5	52	76	110	
3/4"	79	107.5	32	45	94	41.5	52	76	118	
1"	85	115	32	45	101	42.5	52	76	124	

Solenoid Vave Symbol	Valve Type/ Order No	Connection Size	Orifice Size	Pressure				Kv	Seal			Weight	ATEX Coil
	S5078	G	mm	For gas fluids		For liquid fluids		l/min	Viton	NBR	EPDM	kg	C41 C43
	min bar	max bar	min bar	max bar									
	S5078.02.125	3/8"	12.5	0	16	0	16	48	✓	✓	✓	0,68	✓
	S5078.03.145	1/2"	14.5	0	16	0	16	70	✓	✓	✓	0,71	✓
	S5078.04.170	3/4"	17	0	16	0	16	85	✓	✓	✓	0,8	✓
	S5078.05.170	1"	17	0	16	0	16	90	✓	✓	✓	0,97	✓
	S5078.06.300	1 1/4"	30	0	3	0	12	250	✓	✓	✓	3,50	
	S5078.07.390	1 1/2"	39	0	3	0	12	300	✓	✓	✓	3,20	
S5078.08.460	2"	46	0	3	0	12	350	✓	✓	✓	2,98		

Compressor Solenoid Valve S5079 Series (G1/8", G1/4")

GENERAL FEATURES

- Wide pressure range, flow rate and orifices options.
- Solenoid valves are used with filters.
- Solenoid valves can be mounted in any position without affecting its operation.
- Coil to be used in a vertical position.
- TORK series S5079 direct acting plate mounting compressor solenoid valves are 2/2 way, normally closed and have small body size.
- Without manual override, for small body (1/8" and 1/4"), square type body and easy installation

Working temperature: -20°C / +160°C

- On request; manual override
- Don't require any differential pressure.
- On request; solenoid valve can have 4 mounting holes at the bottom of the body.

ELECTRICAL CHARACTERISTICS

Continuous Duty	: ED %100
Coil Insulation Class	: H (180°C)(IEC 85)
Coil Impregnation	: Polyester Fiber Glass
Ambient Temperature	: -20°C, +60°C
Protection Degree	: IP65 (ISO 60529) On request; IP68
Electric Plug Connection	: DIN 46340 3-Poles Connector (DIN 43650)
Connector Specification	: ISO 4400 / EN 175301-803 Form A, Spade Plug (Cable Ø6-8 mm)
Electrical Safety	: IEC 335
Standard Voltages	: AC 12V 15VA, 24V 15VA, 48V 15VA, 230V 15VA, 230V 24VA DC 12V 18W, 24V 18W, 48V 18W, 110V 18W

On request other voltages

Voltages Tolerance : AC -15%, +10% DC -5%, +10%

Frequency : 50 Hz (60 Hz...)

On request; Connector with LED, PWM Socket Specify coil voltage with order

MATERIALS IN CONTACT WITH FLUID

Body	: Brass
Internal Parts	: Stainless Steel
Sealing	: VITON
Shading Ring	: Copper (EN 12735-1)
Seats, Core Tube, Springs	: Stainless Steel

OPTIONS

Female connection: BSP; (On request NPT)

- On request CR-Ni plated, PTFE coated done
- On request Atex (exproof) coil.

TECHNICAL FEATURES

Max. Viscosity : 5°E (-37cST veya mm²/s)

Response Time : Opening time : 30 ms
Closing Time : 30 ms

SEALS FEATURES

NBR : -20°C...+80°C

EPDM : -30°C...+130°C

VITON : -20°C...+160°C

PTFE : -10°C...+160°C

RUBY : -10°C...+160°C



NORMALLY OPEN


2/2 WAY

DIRECT ACTING


$\Delta P=0$



COMPRESSOR



On request; solenoid valve can have 4 mounting holes at the bottom of the body.



Dimensions (mm)

	G	A	B	C	D	E	F	I
1/8"	35	78,5	32	39	68	26,5	35	
1/4"	35	78,5	32	39	68	26,5	35	

Coils	Nominal Values	Cold/ Hot	Inrush	Holding	Current (A)	Surface Temperature (°C)
C40012VDC18W	12VDC 18W	COLD	19,56	19,56	1,63	20
		HOT	14,52	14,52	1,21	106
C40024VDC18W	24VDC 18W	COLD	20,88	20,88	0,87	25
		HOT	14,64	14,64	0,61	116
C40110VDC18W	110VDC 18W	COLD	19,96	19,96	0,18	23
		HOT	13,56	13,56	0,123	115
C40012VAC15VA	12VAC 15VA	COLD	23,81	16,43	1,3	25
		HOT	-	15,86	1,262	79
C40024VAC15VA	24VAC 15VA	COLD	25,82	15,02	0,62	22
		HOT	-	13,91	0,57	81
C40110VAC15VA	110VAC 15VA	COLD	30,65	15,17	0,137	24
		HOT	-	13,96	0,126	80
C40230VAC15VA	230VAC 15VA	COLD	31,4	15,64	0,068	25
		HOT	-	14,41	0,063	80
C40230VAC24VA	230VAC 24VA	COLD	45,1	23,92	0,0154	23
		HOT	-	21,62	0,0154	100

Solenoid Vave Symbol	Valve Type/ Order No	Connection Size	Orifice Size	Pressure min/max		Kv	Seal	Weight
	S5079	G	mm	Bar	Bar	l/min	VITON	kg
	S5079.00.018	1/8"	1.8	0	12	1.6	✓	0,51
	S5079.00.025	1/8"	2.5	0	10	3.2	✓	0,51
	S5079.00.030	1/8"	3	0	5	4.6	✓	0,51
	S5079.01.018	1/4"	1.8	0	12	1.6	✓	0,5
	S5079.01.025	1/4"	2.5	0	10	3.2	✓	0,5
	S5079.01.30	1/4"	3	0	5	4.6	✓	0,5

STANDARDS

• Standard tube connection G (BSP) (ISO 228-1) and other tube connections (NPT (ANSI 1.20.3)) are available on request.

• TORK solenoid valves 97/23/EC, are available for pressure equipment directive (PED) and 2006/95/ECC low voltage directive (LVD).

Not: Please look catalogues for more details